

PRODUCT CLASS

Type C



HIGH TECH SEAMS LINE

Iridium pre-stretch braid with coating

ANIMA : IRIDIUM_78

TECHNICAL
SEWING
BRAID

CORE : Iridium_78 pre-stretch +
poliurethane resin treatment

COVER : Tech Absent
mix



COVER TECH MIX : ABSENT

FIBER CHARACTERISTICS

The fiber's components of this product are : IRIDIUM_78

- Dyneema it's an ultra high molecular weight polyethylene .



FIBER'S PROPERTY	UDM	IRIDIUM 78	-	-	-
Tenacity	gr/den	36,0	-	-	-
Specific gravity	gr/cm ³	0,974	-	-	-
Elongation at break	%	3,5	-	-	-
Tensile modulus	gr/den	1.314	-	-	-
Melting point	°C	147	-	-	-

CORE



IRIDIUM_78

COVER

ABSENT



BRAID CHARACTERISTICS

CORE			COVER (it's a media of the of all fiber's components)	
Tenacity	36	gr/den	Abrasion resistance	gr/den
Creep	0,5	%	Peack of temp.	°C
Module	1314	gr/den	Grip	frict. coeff.
Weight	0,974	gr/cm ³	Weight	gr/cm ³

DISCOUNT SYSTEM			
SHOP		WHOLESALE	
Standard lenght	sc. %	Standard lenght	sc. %
-	-	-	-
-	-	-	-

APPLICATIONS , TECHNICAL DATA , PRICE

- Dyneema resin-coated braid for technical stitching

red	royal			
green	yellow			
white	grey			

∅	weight	breacking load	standard length	custom length	∅	solid colors			
mm	gr/mt	daN	mt	mt	mm	€/pz			
8X 0,30	0,092	22,8	300	-	8X 0,30	34,90 €	-	-	-
8X 0,40	0,162	39,9	300	-	8X 0,40	34,90 €	-	-	-
8X 0,60	0,256	45,5	300	-	8X 0,60	37,40 €	-	-	-
8X 0,70	0,372	89,6	300	-	8X 0,70	37,40 €	-	-	-
12X 0,90	0,559	134,4	300	-	12X 0,90	45,90 €	-	-	-
16X 1,00	0,746	179,2	300	-	16X 1,00	45,90 €	-	-	-
12X 1,20	1,119	210,0	300	-	12X 1,20	74,90 €	-	-	-
16X 1,50	1,493	300,0	300	-	16X 1,50	87,00 €	-	-	-
-	-	-	-	-	-	-	-	-	-
-	-	-	-	-	-	-	-	-	-
-	-	-	-	-	-	-	-	-	-
-	-	-	-	-	-	-	-	-	-
-	-	-	-	-	-	-	-	-	-
-	-	-	-	-	-	-	-	-	-
-	-	-	-	-	-	-	-	-	-
-	-	-	-	-	-	-	-	-	-
-	-	-	-	-	-	-	-	-	-
-	-	-	-	-	-	-	-	-	-
-	-	-	-	-	-	-	-	-	-
-	-	-	-	-	-	-	-	-	-
-	-	-	-	-	-	-	-	-	-

* Linear breaking load in according to DIN EN ISO 2307