

PRODUCT CLASS

Type A


DYNEEMA SK78 CVR

High tech protection cover

DYNEEMA SK78 CVR

CORE : Absent
COVER : Dyneema SK78 (poliurethane resin treatment on request)

CORE : ABSENT



COVER TECH MIX : DYNEEMA SK78



FIBER CHARACTERISTICS


The fiber's components of this product are : **DYNEEMA SK78**

- **Dyneema** it's an ultra high molecular weight polyethylene .



FIBER'S PROPERTY	UDM	DYNEEMA SK78	-	-	-
Tenacity	gr/den	39,8	-	-	-
Specific gravity	gr/cm ³	0,974	-	-	-
Elongation at break	%	3,5	-	-	-
Tensile modulus	gr/den	1.314	-	-	-
Melting point	°C	147	-	-	-

CORE ABSENT



BRAID CHARACTERISTICS

CORE		COVER (it's a media of the of all fiber's components)	
Tenacity	- gr/den	Abrasion resistance	39,8 gr/den
Creep	- %	Peack of temp.	147 °C
Module	- gr/den	Grip	0,06 frict. coeff.
Weight	- gr/cm ³	Weight	0,947 gr/cm ³

DISCOUNT SYSTEM	
SHOP	WHOLESALE
Custom lenght sc. %	Custom lenght sc. %
Standard lenght sc. %	Standard lenght sc. %
-	-

APPLICATIONS , TECHNICAL DATA , PRICE

- Line protection in areas subjected to high abrasion

red	royal			
green	yellow			
black	grey			

size	adapt for protect lines of the following diameters	weight	breacking load	standard lenght	solid colors	-	-	-
		gr/mt	daN	mt	€/mt	-	-	-

1 x 32 (1600)	3	8,0	1.000	100	2,000 €	-	-	-
	4							
	5							

2 x 32 (1600)	5	16,0	2.000	100	4,000 €	-	-	-
	6							
	7							

3 x 32 (1600)	8	24,0	3.000	100	5,750 €	-	-	-
	9							
	10							

* Linear breaking load in according to DIN EN ISO 2307