



**PRODUCT CLASS**

**Type C**

**POLYESTER SEAMS LINE**  
*Pollestere braid with coating*

**POLYESTER SEWING LINE**  
 CORE : Polyester + poliurethane resin treatment  
 COVER : Tech mix Absent

CORE : POLYESTER



COVER TECH MIX : ABSENT


**FIBER CHARACTERISTICS**

The fiber's components of this product are : **POLYESTER HT**

- Polyester it's polymers produced by mixing ethylene glycol and terephthalic acid.



FIBER'S PROPERTY	UDM	POLYESTER HT	-	-	-
Tenacity	gr/den	9,3	-	-	-
Specific gravity	gr/cm <sup>3</sup>	1,38	-	-	-
Elongation at break	%	14,6	-	-	-
Tensile modulus	gr/den	120	-	-	-
Melting point	°C	256	-	-	-



COVER ABSENT



**BRAID CHARACTERISTICS**

CORE			COVER <small>( it's a media of the of all fiber's components )</small>		
Tenacity	9,3 gr/den	Abrasion resistance	-	gr/den	
Creep	10 %	Peack of temp.	-	°C	
Module	120 gr/den	Grip	-	frict. coeff.	
Weight	1,38 gr/cm <sup>3</sup>	Weight	-	gr/cm <sup>3</sup>	

DISCOUNT SYSTEM			
SHOP		WHOLESALER	
Standard lenght	sc. %	Standard lenght	sc. %
-	-	-	-
-	-	-	-

**APPLICATIONS , TECHNICAL DATA , PRICE**

- Polyester resin-coated braid for technical stitching

red	royal		
green	yellow		
black	grey		

∅	weight	breaking load	standard length	custom length	∅	solid colors	€/pz		
mm	gr/mt	daN	mt	mt	mm	€ /pz			
1,00	1,8	22,8	500	on request	1,00	29,00 €	-	-	-
1,50	2,7	39,9	250	on request	1,50	20,00 €	-	-	-
-	-	-	-	-	-	-	-	-	-
-	-	-	-	-	-	-	-	-	-
-	-	-	-	-	-	-	-	-	-
-	-	-	-	-	-	-	-	-	-
-	-	-	-	-	-	-	-	-	-
-	-	-	-	-	-	-	-	-	-
-	-	-	-	-	-	-	-	-	-
-	-	-	-	-	-	-	-	-	-
-	-	-	-	-	-	-	-	-	-
-	-	-	-	-	-	-	-	-	-
-	-	-	-	-	-	-	-	-	-
-	-	-	-	-	-	-	-	-	-
-	-	-	-	-	-	-	-	-	-
-	-	-	-	-	-	-	-	-	-
-	-	-	-	-	-	-	-	-	-
-	-	-	-	-	-	-	-	-	-
-	-	-	-	-	-	-	-	-	-
-	-	-	-	-	-	-	-	-	-

\* Linear breaking load in according to DIN EN ISO 2307