

PRODUCT CLASS

Type C



T6 SQUARE LINE POLY HEMPEX

6 strands hemp effect line

**T6
SQUARE LINE
POLY HEMPEX**

CORE : Polypropylene hemp effect

COVER : Absent

ANIMA : POLYPROPYLENE HT



COVER TECH MIX : ABSENT

FIBER CHARACTERISTICS

The fiber's components of this product are : **POLYPROPYLENE HT**

- **Polypropylene** is a thermoplastic polymer made from the combination of propylene monomers



FIBER'S PROPERTY	UDM	POLYPROPYLENE HT	-	-
Tenacity	gr/den	6,5	-	-
Specific gravity	gr/cm ³	0,910	-	-
Elongation at break	%	20	-	-
Tensile modulus	gr/den	120	-	-
Melting point	°C	164	-	-

CORE CC(C)C POLYPROPYLENE HT

COVER ABSENT




BRAID CHARACTERISTICS

CORE		COVER (it's a media of the of all fiber's components)	
TENACITY	- gr/den	ABRASION RESISTANCE	- gr/den
CREEP	- %	PEAK TEMP.	- °C
MODULE	- gr/den	GRIP	- frict. Coeff.
WEIGHT	- gr/cm ³	LIGHTNESS	- gr/cm ³

DISCOUNT SYSTEM			
SHOP		WHOLESALE	
Standard lenght sc.	%	Standard lenght sc.	%
-	-	-	-
-	-	-	-

APPLICATIONS , TECHNICAL DATA , PRICE

- Decorative synthetic line with amazing hemp effect

			
---	--	--	--

∅	weight	breacking load	standard lenght	custom lenght	∅	hemp	-	-	-
mm	gr/mt	daN	mt	mt	mm	€/mt	-	-	-
10	-	-	-	-	10	-	-	-	-
12	-	-	-	-	12	-	-	-	-
14	79,9	1.755	100	-	14	3,916 €	-	-	-
16	-	-	-	-	16	-	-	-	-
18	-	-	-	-	18	-	-	-	-
20	163,6	3.780	100	-	20	6,545 €	-	-	-
22	-	-	-	-	22	-	-	-	-
24	236,0	5.175	100	-	24	9,439 €	-	-	-
26	-	-	-	-	26	-	-	-	-
28	-	-	-	-	28	-	-	-	-
30	-	-	-	-	30	-	-	-	-
-	-	-	-	-	-	-	-	-	-
-	-	-	-	-	-	-	-	-	-
-	-	-	-	-	-	-	-	-	-
-	-	-	-	-	-	-	-	-	-
-	-	-	-	-	-	-	-	-	-
-	-	-	-	-	-	-	-	-	-
-	-	-	-	-	-	-	-	-	-
-	-	-	-	-	-	-	-	-	-

* Linear breaking load in according to DIN EN ISO 2307

Shock absobtion at 50% of breacking load....12,00%