

PRODUCT CLASS

Type C

AB03 ECO TWISTER THIMBLE SPLICE

3 strand rope hand made spliced

**AB03
ECO TWISTER
EYE SPLICE**

CORE : Polyester MT

COVER : Absent

ANIMA : POLYESTER MT



Abrasion POLYESTER



COVER TECH MIX : ABSENTE

FIBER CHARACTERISTICS


The fiber's components of this product are : **POLYESTER HT**

- **Polyestere** it's polymers produced by mixing ethylene glycol and terephthalic acid.



FIBER'S PROPERTY	UDM	POLYESTER MT	-	-	-
Tenacity	gr/den	4	-	-	-
Specific gravity	gr/cm ³	1,38	-	-	-
Elongation at break	%	30	-	-	-
Tensile modulus	gr/den	90	-	-	-
Melting point	°C	256	-	-	-

CORE



POLYESTER MT

COVER

ABSENT



BRAID CHARACTERISTICS

CORE			COVER (it's a media of the of all fiber's components)		
Tenacity	4	gr/den	Abrasion resistance	-	gr/den
Creep	10	%	Peack of temp.	-	°C
Module	90	gr/den	Grip	-	frict. coeff.
Weight	1,38	gr/cm3	Weight	-	gr/cm3

DISCOUNT SYSTEM

SHOP			WHOLESALE		
Price x pc.	sc.	%	Price x pc.	sc.	%
-	-	-	-	-	-
-	-	-	-	-	-

APPLICATIONS , TECHNICAL DATA , PRICE

- Mooring line with inox thimble splice

	white	black	-	-

∅	weight	breacking load	standard lenght	-	∅	white	black	-	-
mm	gr/mt	daN	mt	-	mm	€/pz	€/pz	-	-
10	69,0	1.230	6	-	10	20,14 €	20,56 €	-	-
12	95,0	1.360	6	-	12	22,71 €	23,28 €	-	-
12	95,0	1.360	8	-	12	24,34 €	25,07 €	-	-
14	138,0	2.010	8	-	14	30,66 €	31,72 €	-	-
14	138,0	2.010	12	-	14	35,39 €	36,93 €	-	-
16	174,0	2.430	8	-	16	34,44 €	35,78 €	-	-
16	174,0	2.430	12	-	16	40,41 €	42,35 €	-	-
18	221,0	3.150	12	-	18	58,65 €	61,12 €	-	-
20	264,0	3.830	12	-	20	67,45 €	70,39 €	-	-
22	310,0	4.610	12	-	22	79,58 €	83,04 €	-	-
24	368,0	5.520	15	-	24	115,52 €	120,57 €	-	-
26	423,0	6.150	15	-	26	124,07 €	129,88 €	-	-
28	520,0	7.200	15	-	28	148,39 €	155,52 €	-	-
-	-	-	-	-	-	-	-	-	-
-	-	-	-	-	-	-	-	-	-
-	-	-	-	-	-	-	-	-	-
-	-	-	-	-	-	-	-	-	-
-	-	-	-	-	-	-	-	-	-

Shock absobtion at 50% of breacking load....12,00%

* Linear breaking load in according to DIN EN ISO 2307