

PRODUCT CLASS

Type C



**AB03 ECO TWISTER
ROPE / CHAIN BARBOTIN
Rope / chain hand made splice**

**AB03
ECO TWISTER
EYE SPLICE**
 CORE : Polyester MT
 COVER : Absent

CORE : POLYESTER HT



FIBER CHARACTERISTICS

The fiber's components of this product are : **POLYESTER HT**

- **Polyestere** it's polymers produced by mixing ethylene glycol and terephthalic acid.



FIBER'S PROPERTY	UDM	POLYESTER MT	-	-	-
Tenacity	gr/den	4	-	-	-
Specific gravity	gr/cm3	1,38	-	-	-
Elongation at break	%	30	-	-	-
Tensile modulus	gr/den	90	-	-	-
Melting point	°C	256	-	-	-

COVER TECH MIX : ABSENT

CHAIN : GALVANIZED



COVER ABSENT



BRAID CHARACTERISTICS

CORE			COVER (it's a media of the of all fiber's		
Tenacity	4 gr/den	4 gr/den	Abrasion resistance	-	gr/den
Creep	10 %	10 %	Peack of temp.	-	°C
Module	90 gr/den	90 gr/den	Grip	-	frict. coeff.
Weight	1,38 gr/cm3	1,38 gr/cm3	Weight	-	gr/cm3

DISCOUNT SYSTEM					
SHOP			WHOLESALE		
Price x pc.	sc.	%	Price x pc.	sc.	%
-	-	-	-	-	-
-	-	-	-	-	-

APPLICATIONS , TECHNICAL DATA , PRICE

- Anchoring line with galvanized chain splice



∅	weight rope	breacking load rope	total lenght	rope lenght	chain lenght	∅	white	black	-	-
mm - inch	gr/mt	daN	mt	mt	mt	mm	€/pz	€/pz	-	-
12,6	95,0	∅12,6 x 40 mt	∅6 x 10 mt	-	-	12,6	131,60 €	134,86 €	-	-
-	-	-	-	-	-	-	-	-	-	-
14,2	138,0	∅12,6 x 50 mt	∅8 x 8 mt	-	-	14,2	192,08 €	198,00 €	-	-
-	-	-	-	-	-	-	-	-	-	-
-	-	-	-	-	-	-	-	-	-	-
-	-	-	-	-	-	-	-	-	-	-
-	-	-	-	-	-	-	-	-	-	-
-	-	-	-	-	-	-	-	-	-	-
-	-	-	-	-	-	-	-	-	-	-
-	-	-	-	-	-	-	-	-	-	-
-	-	-	-	-	-	-	-	-	-	-
-	-	-	-	-	-	-	-	-	-	-
-	-	-	-	-	-	-	-	-	-	-
-	-	-	-	-	-	-	-	-	-	-
-	-	-	-	-	-	-	-	-	-	-
-	-	-	-	-	-	-	-	-	-	-
-	-	-	-	-	-	-	-	-	-	-
-	-	-	-	-	-	-	-	-	-	-
-	-	-	-	-	-	-	-	-	-	-

Shock absobtion at 50% of breacking load....12,00% * Linear breaking load in according to DIN EN ISO 2307