



# PRODUCT CLASS

**Type A**



# SK78 UNI STROP

**7 loop braided core + cover dyneema**

**DYNEEMA SK78  
UNI LOOP**

**CORE :** Dyneema SK78 pre-stretch + poliurethane resin treatment  
**COVER :** Tech mix Dyneema SK78

**CORE :** DYNEEMA SK78  
( PRE-STRETCH HPT + PU RESIN TREATMENT )



**COVER TECH MIX :** DYNEEMA SK78



## FIBER CHARACTERISTICS

The fiber's components of this product are : **DYNEEMA SK78**

- **Dyneema** it's an ultra high molecular weight polyethylene .



FIBER'S PROPERTY	UDM	DYNEEMA SK78	-	-	-
Tenacity	gr/den	39,8	-	-	-
Specific gravity	gr/cm <sup>3</sup>	0,974	-	-	-
Elongation at break	%	3,5	-	-	-
Tensile modulus	gr/den	1.314	-	-	-
Melting point	°C	147	-	-	-



## BRAID CHARACTERISTICS

CORE			COVER ( it's a media of the of all fiber's components )		
Tenacity	39,8	gr/den	Abrasion resistance	39,8	gr/den
Creep	0,5	%	Peack of temp.	147	°C
Module	1.314	gr/den	Grip	0,06	frict. coeff.
Weight	0,974	gr/cm <sup>3</sup>	Weight	0,947	gr/cm <sup>3</sup>

DISCOUNT SYSTEM	
SHOP	WHOLESALE
Custom lenght sc. %	Custom lenght sc. %
Standard lenght sc. %	Standard lenght sc. %
-	-

## APPLICATIONS , TECHNICAL DATA , PRICE

- Extreme performance strop

red	royal			
green	yellow			
black	grey			

∅	weight	working load	breacking load	measure	custom lenght	∅	solid colors			
mm	gr/mt	daN	daN	cm	mt	mm	€/pz			
1F 1-32 6 X7	0,0	1.000	3.000	5 - 30 - 5	on request	6	40 €	-	-	-
1F 1-32 6 X7	0,0	1.000	3.000	5 - 60 - 5	on request	6	45 €	-	-	-
1F 1-32 6 X7	0,0	1.000	3.000	5 - 100 - 5	on request	6	50 €	-	-	-
-	-	-	-	-	-	-	-	-	-	-
1,5F 1-32 8 X7	0,0	2.000	6.000	5 - 30 - 5	on request	8	45 €	-	-	-
1,5F 1-32 8 X7	0,0	2.000	6.000	5 - 60 - 5	on request	8	50 €	-	-	-
1,5F 1-32 8 X7	0,0	2.000	6.000	5 - 100 - 5	on request	8	55 €	-	-	-
-	-	-	-	-	-	-	-	-	-	-
2F 2-32 10 X7	0,0	2.500	7.500	5 - 30 - 5	on request	10	50 €	-	-	-
2F 2-32 10 X7	0,0	2.500	7.500	5 - 60 - 5	on request	10	55 €	-	-	-
2F 2-32 10 X7	0,0	2.500	7.500	5 - 100 - 5	on request	10	60 €	-	-	-
-	-	-	-	-	-	-	-	-	-	-
3F 3-32 12 X7	0,0	4.000	12.000	5 - 30 - 5	on request	12	55 €	-	-	-
3F 3-32 12 X7	0,0	4.000	12.000	5 - 60 - 5	on request	12	60 €	-	-	-
3F 3-32 12 X7	0,0	4.000	12.000	5 - 100 - 5	on request	12	65 €	-	-	-

Stretch at 30% of breacking load....2,15%  
Stretch at breacking load.....3,50%

\* Linear breaking load in according to DIN EN ISO 2307