PRODUCT CLASS	Type A

SK78 BRD DOG BONE

Braided dog bone

DYNEEMA SK78 BRD DOG BONE

- **CORE :** Dyneema SK78 pre-stretch + poliurethane resin treatment
- **COVER :** **Tech mix** Absent

CORE : DYNEEMA SK78
(PRE-STRETCH HPT + PU RESIN TREATMENT)

---- Tenacity ---- Dyneema SK78

HAND MADE

COVER TECH MIX : ABSENT

FIBER CHARACTERISTICS

The fiber's components of this product are : **DYNEEMA SK78**

- **Dyneema** it's an ultra high molecular weight polyethylene .

FIBER'S PROPERTY	UDM	*DYNEEMA SK78*	-	-	-
Tenacity	gr/den	39,8	-	-	-
Specific gravity	gr/cm^3	0,974	-	-	-
Elongation at break	%	3,5	-	-	-
Tensile modulus	gr/den	1.314	-	-	-
Melting point	°C	147	-	-	-

COR — DYNEEMA SK78

COVER — ABSENT

FLOATING

BRAID CHARACTERISTICS

CORE			COVER (it's a media of the of all fiber's components)		
Tenacity	39,8	gr/den	Abrasion resistance	-	gr/den
Creep	0,5	%	Peack of temp.	-	°C
Module	1.314	gr/den	Grip	-	frict. coeff.
Weight	0,974	gr/cm^3	Weight	-	gr/cm^3

DISCOUNT SYSTEM	
SHOP	*WHOLESALER*
Custom lenght sc. %	Custom lenght sc. %
Standard lenght sc. %	Standard lenght sc. %
-	-

APPLICATIONS , TECHNICAL DATA , PRICE

- High performance dog bone

red, royal, green, yallow, black, grey

Ø	weight	working load	breacking load	measure	custom lenght	Ø	solid colors	-	-	-
mm	gr/mt	daN	daN	cm	mt	mm	€/pz	-	-	-
7F 6	0,0	1.000	3.000	13	on request	6	18,0	-	-	-
10F 8	0,0	2.000	6.000	15	on request	8	21,0	-	-	-
16F 10	0,0	3.000	9.000	17	on request	10	25,0	-	-	-
21F 12	0,0	5.000	15.000	18	on request	12	30,0	-	-	-
-	-	-	-	-	-	-	-	-	-	-
-	-	-	-	-	-	-	-	-	-	-
-	-	-	-	-	-	-	-	-	-	-
-	-	-	-	-	-	-	-	-	-	-
-	-	-	-	-	-	-	-	-	-	-
-	-	-	-	-	-	-	-	-	-	-
-	-	-	-	-	-	-	-	-	-	-
-	-	-	-	-	-	-	-	-	-	-
-	-	-	-	-	-	-	-	-	-	-
-	-	-	-	-	-	-	-	-	-	-
-	-	-	-	-	-	-	-	-	-	-
-	-	-	-	-	-	-	-	-	-	-
-	-	-	-	-	-	-	-	-	-	-
-	-	-	-	-	-	-	-	-	-	-

Stretch at 30% of breacking load....2,15%
Stretch at breacking load.....3,50%

* Linear breaking load in according to DIN EN ISO 2307